

ICEMAKER VALVES

DUAL ICEMAKER VALVES

Body Material for all Valves is Polypro
 Operating Pressure Range for all Valves is 20-120 PSI
 Max. Water Temp. for all valves is 160°F

ORDERING DATA

UNI-LINE ORDER NO.	FLOW RATE IN GPMS		INLET		OUTLET 1 - ICEMAKER		OUTLET 2 - DOOR		COILS		(1)	(2)
	(1)	(2)	SIZE	TYPE	SIZE	TYPE	SIZE	TYPE	VOLTS	HZ	W	W
IMV-500	0.125	0.500	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	5/8"-20	UN-2	120	50/60	15	10
IMV-501	0.220	0.550	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	15	15
IMV-502	0.125	0.500	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	7/16"-20	UNF-2A	120	50/60	15	10
IMV-503	0.200	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	15	15
IMV-505	0.200	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	50	15
IMV-506	0.250	0.550	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	15	15
IMV-510	0.220	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	15	15
IMV-512	0.220	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	15	15
IMV-513	0.220	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	100	15
IMV-516	0.125	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	7/16"-20	UNF-2A	120	50/60	15	15
IMV-517	0.290	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	50	15
IMV-700	0.290	NO FW	7/16"-24	UNS-2A	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	50/60	15	10
IMV-701	0.290	NO FW	7/16"-24	UNS-2A	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	60	15	10
IMV-702	0.250	NO FW	7/16"-24	UNS-2A	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	60	15	10
IMV-800	0.290	NO FW	3/4"-11 1/2	NHT	7/16"-20	UNF-2A	1/2"-20	UNF-2A	120	60	20	15