

## ORDERING DATA

UNI-LINE ORDER NO.	SWITCH TYPE	HP	WIRING† DIAG. #	AC LINE VOLTS	ENCLOSURE MATERIAL	ENCLOSURE TYPE	TYPE OF MOUNT	DIMENSIONS		
								W	H	D
<b>TRI-TIMERS—EL7200 SERIES</b>										
EL7200/120V	SPDT		3, 4	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	8-1/8"	3"
EL7200/208-240V	SPDT		3, 4	208-240	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	8-1/8"	3"
EL7200PC/120V	SPDT		3, 4	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	9"	3-7/8"
EL7200PC/208-240V	SPDT		3, 4	208-240	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	9"	3-7/8"
<b>TRI-TIMERS—EL7100 SERIES</b>										
EL7100/120V	SPDT		9	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	8-1/8"	3"
EL7100/208-240V	SPDT		9	208-240	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	8-1/8"	3"
EL7100PC/120V	SPDT		9	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	9"	3-7/8"
EL7100PC/208-240V	SPDT		9	208-240	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	9"	3-7/8"
<b>TRI-TIMERS—EC72D SERIES</b>										
EC72D/12VDC*	SPDT		10	12VDC	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"
EC72D/24V*	SPDT		10	24	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"
EC72D/120V	SPDT		10	100-120	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"
EC72D/240V	SPDT		10	200-240	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"
<b>TRI-TIMERS—EC74/50S SERIES</b>										
EC74/50S/24V*	SPDT		11	24	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-5/16"	8-1/2"	3-13/16"
EC74/50S/120V	SPDT		11	100-120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-5/16"	8-1/2"	3-13/16"
EC74/50S/240V	SPDT		11	200-240	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-5/16"	8-1/2"	3-13/16"
<b>TRI-TIMERS—EC71D/18S SERIES</b>										
EC71D/18S/24V*	SPDT		12	24	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"
EC71D/18S/120V	SPDT		12	120	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"
EC71D/18S/240V	SPDT		12	208-240	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"

† See wiring diagrams on pages G35-G41.

\*Not recognized under UL or CSA component program

Frequency: 50/60 Hz Power consumption: 4VA

Wiring terminals: Power input and relay contact terminals can accommodate 10-16 AWG on EL7200 series and EL7100 series