

## 24-HOUR TIMERS

### ORDERING DATA

UNI-LINE ORDER NO.	SWITCH TYPE	HP	WIRING† DIAG.#	AC LINE VOLTS	ENCLOSURE MATERIAL	ENCLOSURE TYPE	TYPE OF MOUNT	DIMENSIONS		
								W	H	D
<b>24-HOUR TIMERS—EC4000 SERIES</b>										
EC4000/120V	SPDT	1	19	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	7-7/8"	3"
EC4000PC/120V	SPDT	1	19	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
EC4000PC/120V-RT	SPDT	1	19	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
EC4000/208-277V	SPDT	1	19	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	7-7/8"	3"
EC4000PC/208-277V	SPDT	1	19	208-277	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
EC4004/120V	SPST	2	14	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	7-7/8"	3"
EC4004PC/120V-RT	SPST	2	14	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	7-7/8"	3"
EC4004PC/120V	SPST	2	14	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
EC4004PC/120V-RT	SPST	2	14	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
EC4004/208-277V	SPST	2	14	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	7-7/8"	3"
EC4004/208-277V-RT	SPST	2	14	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/4"	7-7/8"	3"
EC4004/208-277V	SPST	2	14	208-277	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
EC4004PC/208-277V-RT	SPST	2	14	208-277	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
EC4005PC/120, 208-240V-RT*	DPST	3	16	120/208-240	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/8"	3-7/8"
<b>24-HOUR TIMERS—EC11D SERIES</b>										
EC11D/120V•	SPDT		29	100-120	NON-METALLIC	N/A	DIN RAIL MOUNT	4-1/2"	4"	3"
<b>24-HOUR TIMERS—P100 SERIES</b>										
P101	SPST	2	20	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P101M	SPST	2	20	120	MOVEMENT ONLY	N/A	N/A			
P101P	SPST	2	20	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P101-RT	SPST	2	20	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P101PC-RT	SPST	2	20	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P101-00R	SPST	2		120	MECHANISM ONLY REPLACES INTERMATIC T101	—	—	—	—	—
P103	DPST	2	21, 22	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P103M	DPST	2	21, 22	120	MOVEMENT ONLY	N/A	N/A			
P103P	DPST	2	21, 22	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P103-RT	DPST	2	21, 22	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P103PC-RT	DPST	2	21, 22	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P104	DPST	3	21, 22	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P104M	DPST	3	21, 22	208-277	MOVEMENT ONLY	N/A	N/A			
P104P	DPST	3	21, 22	208-277	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P104-RT	DPST	3	21, 22	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P104PC-RT	DPST	3	21, 22	208-277	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P104-71R	DPST	3		208-277	MECHANISM ONLY REPLACES INTERMATIC T104	—	—	—	—	—
<b>WITH SKIP-A-DAY</b>										
P101-S	SPST	2	20	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P101P-S	SPST	2	20	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P103-S	DPST	2	21, 22	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P103P-S	DPST	2	21, 22	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
P104-S	DPST	3	21, 22	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
P104P-S	DPST	3	21, 22	208-277	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"

\*1 Hp at 120 Vac, 3 Hp at 240 Vac  
 • Frequency: 50/60 Hz for EC4000 and EC11D series  
 Power consumption for EC4000 series: 4VA  
 Models with suffix "M" in P100 series are recognized under the component program of UL and CSA

Frequency for P100 series: 60 Hz Amp: 40 Amp T: 40 VA: 1000  
 P100 series furnished with 2 sets of ON/OFF trippers  
 For P100 series: P is plastic, PC is plastic enclosure with clear-view cover, S is Skip-A-Day, M is movement  
 † See wiring diagrams on pages G35-G41.