

24-HOUR TIMERS

ORDERING DATA

UNI-LINE ORDER NO.	SWITCH TYPE	HP	WIRING† DIAG. #	AC LINE VOLTS	ENCLOSURE MATERIAL	ENCLOSURE TYPE	TYPE OF MOUNT	DIMENSIONS		
								W	H	D
4000 SERIES—NEMA 1 INDOOR METAL ENCLOSURE										
4001-00	SPST	2	24	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4001-00-RT	SPST	2	24	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4001-00B	SPST	2	24	120	BRACKET	N/A	N/A			
4001-00M	SPDT	2	25, 27	120	MOVEMENT ONLY	N/A	N/A			
4002-71	SPDT	2	25, 27	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4002-71B	SPDT	2	25, 27	208-277	BRACKET	N/A	N/A			
4003-00	DPST	2	23, 26	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4003-00-RT	DPST	2	23, 26	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4003-00M	DPST	2	23, 26	120	MOVEMENT ONLY	N/A	N/A			
4004-71	DPST	2	23, 26	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4004-71-RT	DPST	2	23, 26	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4004-71B	DPST	2	23, 26	208-277	BRACKET	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4004-71M	DPST	2	23, 26	208-277	MOVEMENT ONLY	N/A	N/A			
4005-00B	SPDT	2	25, 27	120	BRACKET	N/A	N/A			
WITH SKIP-A-DAY										
4003-00S	DPST	2	23, 26	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4003-00SB	DPST	2	23, 26	120	BRACKET	N/A	N/A			
4003-00SM	DPST	2	23, 26	120	MOVEMENT ONLY	N/A	N/A			
4004-06S	DPST	—	23, 26	24	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4004-71S	DPST	2	23, 26	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4005-00S	SPDT	2	25, 27	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4005-00SB	SPDT	2	25, 27	120	BRACKET	N/A	N/A			
4006-71S	SPDT	2	25, 27	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4007-06S	SPDT	—	25, 27	24	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4007-06SB	SPDT	—	25, 27	24	BRACKET	N/A	N/A			
LEAVES LOAD ON DURING DAYS SCHEDULED TO BE SKIPPED										
4008-20S	DPST	2	23, 26	208-277	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/8"	8-1/2"	2-1/4"
4010 SERIES—NEMA 3 INDOOR/OUTDOOR METAL OR NEMA 3R NON-METALLIC ENCLOSURE										
4011-00	SPST	2	24	120	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT			
4011-00P	SPST	2	24	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
4011-00PC-RT	SPST	2	24	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
4013-00	DPST	2	23, 26	120	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT			
4013-00P	DPST	2	23, 26	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
4013-00PC-RT	DPST	2	23, 26	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-9/16"	8-1/2"	3-3/4"
4014-71	DPST	2	23, 26	208-277	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT			
WITH SKIP-A-DAY										
4013-00S	DPST	2	23, 26	120	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT			
4014-71S	DPST	2	23, 26	208-277	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT			
24-HOUR TIMERS—WB100 SERIES										
WB101	SPST	1	24	120	WHITE WALL PLATE	N/A	WALL BOX MOUNT	2-3/4"	4-1/2"	2-1/2"
WB102	SPST	1	24	120	WHITE WALL PLATE	N/A	WALL BOX MOUNT	4-1/2"	4-1/2"	2-1/2"
WB103	SPST	1	24	120	WHITE WALL PLATE	N/A	WALL BOX MOUNT	4-9/16"	4-1/2"	2-1/2"

Frequency: 60 Hz for 4000 series, 50/60 Hz for EC11D
Switch rating per pole for 4000 series: 40 amp, 40 ampT, 690 VA
Models with suffix "B" or "M" are recognized under the component program of UL and CSA
S is Skip-A-Day
4000 series is furnished with 1 set of ON/OFF trippers
Power consumption for EC11D: 4VA
† See wiring diagram on pages G35-G41.