

INDUSTRIAL PROCESS CONTROLS

ORDERING DATA

UNI-LINE ORDER NO.	SWITCH TYPE	HP	WIRING† DIAG. #	AC LINE VOLTS	GRADUATION	RANGE	ENCLOSURE MATERIAL	ENCLOSURE TYPE	DIMENSIONS			
									W	H	D	
PROCESS CONTROLS—EJW SERIES												
EJW**	SPST	1	20	30	120-240	VARIOUS	15 SEC-24 HRS	NON-METALLIC (I/O)	NEMA 4X	4-3/4"	4-3/4"	3"
EJW-M**	SPST	2	20	30	120-240	VARIOUS	15 SEC-24 HRS	MECHANISM ONLY	—	4-3/4"	4-3/4"	1"

UNI-LINE ORDER NO.	SWITCH TYPE	HP	WIRING† DIAG. #	AC LINE VOLTS	GRADUATION	RANGE	ENCLOSURE MATERIAL	ENCLOSURE TYPE	DIMENSIONS			
									W	H	D	
PROCESS CONTROLS—JW SERIES												
JW5-00	SPST	1/2	31, 32	120	10 SECONDS	5 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	
JW5-00PC	SPST	1/2	31, 32	120	10 SECONDS	5 MINUTES	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	6-1/2"	9"	3-7/8"	
JW5-20*	SPST	1/2	31, 32	208-240	10 SECONDS	5 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	
JW5-20PC*	SPST	1/2	31, 32	208-240	10 SECONDS	5 MINUTES	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	6-1/2"	9"	3-7/8"	
JW10-00	SPST	1/2	31, 32	120	12 SECONDS	10 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	
JW10-00PC	SPST	1/2	31, 32	120	12 SECONDS	10 MINUTES	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	6-1/2"	9"	3-7/8"	
JW10-20*	SPST	1/2	31, 32	208-240	12 SECONDS	10 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	
JW10-20PC*	SPST	1/2	31, 32	208-240	12 SECONDS	10 MINUTES	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	6-1/2"	9"	3-7/8"	
JW30-00	SPST	1/2	31, 32	120	30 SECONDS	30 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	
JW30-20*	SPST	1/2	31, 32	208-240	30 SECONDS	30 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	
JW60-00	SPST	1/2	31, 32	120	60 SECONDS	60 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	
JW60-20*	SPST	1/2	31, 32	208-240	60 SECONDS	60 MINUTES	METAL (INDOOR)	NEMA 1	3-1/2"	5-1/8"	2-7/8"	

*Not UL or CSA listed

**NO - 20 amp, NC - 10 amp

Switch rating per pole is 15 amp

AC line: 60 Hz

† See wiring diagram on pages G35-G41.

ORDERING DATA

UNI-LINE ORDER NO.	SWITCH TYPE	HP	WIRING† DIAG. #	AC LINE VOLTS	ENCLOSURE MATERIAL	ENCLOSURE TYPE	TYPE OF MOUNT	DIMENSIONS		
								W	H	D
PROCESS CONTROLS—1015 SERIES										
1015-00RS	SPDT	—	35	120	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT	5-3/8"	9-5/8"	4-3/16"
1015-00RSB	SPDT	—	33	208-240	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT	5-3/8"	9-5/8"	4-3/16"
1015-40TS	SPDT	—	34	480	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT	5-3/8"	9-5/8"	4-3/16"
PROCESS CONTROLS—8025 SERIES										
8025-00	2 NO-1NC	2	38	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-3/8"	7-11/16"	3-13/16"
8025-00P	2 NO-1NC	2	38	120	NON-METALLIC WITH CLEAR-VIEW COVER (INDOOR/OUTDOOR)	NEMA 3R	ENCLOSURE MOUNT	6-1/2"	9"	3-7/8"
8025-20	2 NO-1NC	2	38	208-240	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-3/8"	7-11/16"	3-13/16"
PROCESS CONTROLS—42000 SERIES										
42011-00	SPST	1	36	120	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT	5-3/8"	9-5/8"	4-3/16"
42011-20	SPST	1	36	208-240	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT	5-3/8"	9-5/8"	4-3/16"
42013-00	DPST	1	37	120	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT	5-3/8"	9-5/8"	4-3/16"
42013-20	DPST	2	37	208-240	METAL (INDOOR/OUTDOOR)	NEMA 3	ENCLOSURE MOUNT	5-3/8"	9-5/8"	4-3/16"
PROCESS CONTROLS—44000 SERIES										
44001-00	SPST	1	25	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/16"	7-7/8"	2-15/16"
44005-00	SPDT	1	25	120	METAL (INDOOR)	NEMA 1	ENCLOSURE MOUNT	4-1/16"	7-7/8"	2-15/16"

Models with suffix "B" in 1015 series are recognized under the component program of UL and CSA

Models with suffix "P" in 8025 series are plastic

8025 series furnished with 4 dial pins

Frequency for 8025 and 44000 series: 60 Hz

Frequency for 42000 series: 50 Hz

Switch rating per pole for 44000 series: 40 amp, 40 ampT, 690 VA

† See wiring diagram on pages G35-G41.