

## TECHNICAL INFORMATION

TL Twist-lock control  
 CW Conduit-wired with manual slider  
 LB Single-gang switch plates  
 PN Wire-in swivel tube

*Override*  
 Loads remain ON for 15 seconds during power failures.

*Sensory Inputs*  
 Sensors automatically react to light. Units turn ON when no light is present. Units turn OFF when light is present.

### TIMEKEEPING CAPABILITIES

Cadmium cell that reacts to natural and artificial light.

### PROGRAMMING ATTRIBUTES AND CAPABILITIES

#### Events/Set Points

Turn ON when light isn't present and turn OFF when light is present.

#### Holidays

N/A

### HARDWARE ATTRIBUTES

#### Carry-over

N/A

#### Display

N/A

#### Enclosure

N/A

## ORDERING DATA

| UNI-LINE<br>ORDER NO.  | WIRING†<br>DIAG. # | AC LINE<br>VOLTS | SWITCH RATING PER POLE |            |      | LIGHT LEVELS |     | DIMENSIONS |        |          |          |
|--|--------------------|------------------|------------------------|------------|------|--------------|-----|------------|--------|----------|----------|
|  |                    |                  | AMP                    | TUNGSTEN W | AMP  | BALLAST VA   | ON  | OFF        | W      | H        | D        |
| <b>TL SERIES—LOCKING TYPE</b>  |                    |                  |                        |            |      |              |     |            |        |          |          |
| TL201-00   | 48                 | 120              | 8.3                    | 1000       | —    | 1800         | 1.5 | 6          | 2-7/8" | —        | 1-7/8"   |
| TL201-70   | 49, 50             | 120-277          | 3.6                    | 1000       | —    | 1800         | 1.5 | 6          | 2-7/8" | —        | 1-7/8"   |
| TL201-71   | 46                 | 208-277          | 3.6                    | 1000       | —    | 1800         | 1.5 | 6          | 2-7/8" | —        | 1-7/8"   |
| TL-201-00-RT   | 48                 | 120              | 8.3                    | 1000       | —    | 1800         | 1.5 | 6          | 2-7/8" | —        | 1-7/8"   |
| TL301-00   | 48                 | 120              | —                      | 1000       | —    | 1800         | 1.5 | 6          | 2-7/8" | —        | 1-7/8"   |
| TL301-71   | 46                 | 208-277          | —                      | 1000       | —    | 1800         | 1.5 | 6          | 2-7/8" | —        | 1-7/8"   |
| TL301-80   | —                  | 480              | —                      | 1000       | —    | 1800         | 1.5 | 6          | 2-7/8" | —        | 1-7/8"   |
| TL401-70   | 49, 50             | 120-277          | —                      | 1000       | —    | 1800         | 3.0 | 1.8        | 2-7/8" | —        | 1-7/8"   |
| TL501-00   | 48                 | 120              | —                      | 1000       | —    | 1800         | 1.5 | 3.0        | 2-7/8" | —        | 1-7/8"   |
| <b>SC SERIES—SHORTING CAP</b>  |                    |                  |                        |            |      |              |     |            |        |          |          |
| SC201-99*  | N/A                | N/A              | N/A                    | N/A        | N/A  | N/A          | N/A | N/A        | N/A    | N/A      | N/A      |
| <b>TB SERIES—TWIST-LOCK BASE</b>   |                    |                  |                        |            |      |              |     |            |        |          |          |
| TB201-99*  | 47                 | N/A              | N/A                    | N/A        | N/A  | N/A          | N/A | N/A        | N/A    | N/A      | N/A      |
| <b>CW SERIES—CONDUIT-WIRED PHOTO CONTROL MANUALLY ADJUSTABLE LEVEL SLIDE</b> |                    |                  |                        |            |      |              |     |            |        |          |          |
| CW201-00   | 48                 | 120              | 16.5                   | 2000       | 15.8 | 1900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW201-00-RT  | 48                 | 120              | 16.5                   | 2000       | 15.8 | 1900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW201-70   | 49, 50             | 120-277          | 7.0                    | 2000       | 6.6  | 1900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW201-71   | 46                 | 208-277          | 7.2                    | 2000       | 6.8  | 1900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW201S-00  | 48                 | 120              | 16.5                   | 2000       | 15.8 | 1900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW201S-71  | 46                 | 240              | 16.5                   | 2000       | 15.8 | 1900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW302-00*  | 48                 | 120              | 25                     | 3000       | 21   | 2500         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW302-70   | —                  | 120              | —                      | 3000       | —    | 2900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| CW302-71   | 48                 | 208-277          | —                      | 2000       | —    | 1900         | 1.5 | 10         | 2"     | 1-15/16" | 2-15/16" |
| <b>LB SERIES—WIRE-IN TYPE, 5/8" NYLON LOCK NUT</b>                           |                    |                  |                        |            |      |              |     |            |        |          |          |
| LB201-00   | 48                 | 120              | 10.0                   | 1800       | 9.1  | 1100         | 1.5 | 10         | 1-1/8" | 2"       | 1-5/8"   |
| LB201-00-RT  | 48                 | 120              | 10.0                   | 1800       | 9.1  | 1100         | 1.5 | 10         | 1-1/8" | 2"       | 1-5/8"   |
| LB201-71   | 46                 | 208-277          | 4.3                    | 1200       | 3.9  | 1100         | 1.5 | 10         | 1-1/8" | 2"       | 1-5/8"   |
| LB201P-00  | 48                 | 120              | 10.0                   | —          | 9.1  | 1100         | 1.5 | 10         | 1-1/8" | 2"       | 1-5/8"   |
| LB201W-00  | 48                 | 120              | 10.0                   | —          | 9.1  | 1100         | 1.5 | 10         | 1-1/8" | 2"       | 1-5/8"   |
| LB201W-00-RT   | 48                 | 120              | 10.0                   | —          | 9.1  | 1100         | 1.5 | 10         | 1-1/8" | 2"       | 1-5/8"   |
| LB301-00   | 48                 | 120              | 2.5                    | —          | 7.0  | 1100         | .5  | 7          | 1-1/8" | 2"       | 1-5/8"   |
| LB301-71   | 46                 | 208-277          | —                      | 1200       | —    | 1100         | —   | —          | 1-1/8" | 2"       | 1-5/8"   |
| <b>PN SERIES—WIRE-IN WITH SWIVEL</b>   |                    |                  |                        |            |      |              |     |            |        |          |          |
| PN201-00   | 48                 | 120              | 10.0                   | 1200       | 9.1  | 1100         | 3   | 10         | 1-1/4" | 3-3/4"   | —        |
| PN-201-00-RT   | 48                 | 120              | 10.0                   | 1200       | 9.1  | 1100         | 3   | 10         | 1-1/4" | 3-3/4"   | —        |

\*Not listed at UL or CSA

Switch type: SPST

Frequency: 60 Hz

Models with suffix "P" is post mount, "S" is swivel, "W" is wall plate

See wiring diagram on pages G35-G41.