

Our Quad Controls give you 4 outstanding scheduling options in state-of-the-art timed switch controls. You get 24-hour, 7-day, 365-day control, and AstroDial SunTracker™ in a single unit. They are available with 1 to 12 SPDT relays and in NEMA 1 drawn steel enclosures for indoor use.

## FEATURES

- **No Batteries to Change** Minimum 96 hours of battery-free carry-over protects against power outages.
- **Respond to Environmental Conditions** 32 sensor events automatically detect external changes and augment time control capabilities.
- **Meet Your Sophisticated Needs** Up to 128 ON/OFF events accommodate all your scheduling requirements.
- **Automatic Daylight Savings Time Feature** Clocks don't have to be reset for seasonal changes.
- **Leap Year Adjustment** Units automatically adjust daily schedule to stay in sync with calendar.
- **AstroDial SunTracker™** Devices don't require additional photocell and associated maintenance.
- **Worry-free Holiday Programming** 30 holiday durations or 10 holiday durations make schedule variations hassle-free.
- **Convenient Remote Programming** You can modify the program quickly and easily from a laptop or desktop computer.
- **Precise Control** 4 user-defined duty cycles and durations are available from 1 second to 23 hours, 59 minutes, 59 seconds.
- **Consolidate Programming** You can synchronize multiple time controls with a single unit.

## EL712

- 12 SPDT relays
- 8 external inputs allow sensors (see accessories) to automatically adjust to changes in environmental conditions
- Lithium battery provides 1 year of carry-over for extra protection with capacitor
- RS-232 port and Pecosoft.EL software are available for convenient remote programming (see accessories)
- Stagger-up feature turns loads ON separately after power outages to prevent power surges
- Title 24 certified
- Unit dimensions are 14-5/16" W x 15-1/8" H x 6-1/8" D



EL712

## EL74

- 4 SPDT relays
- 4 external inputs allow sensors (see accessories) to automatically adjust to changes in environmental conditions
- 1 year of carry-over available with lithium battery and capacitor
- RS-232 port and Pecosoft.EL software provide remote programming capabilities (see accessories)
- Stagger-up feature activates loads separately after power outages to protect against power surges
- Title 24 certified
- Unit dimensions are 7-3/8" W x 10-7/8" H x 3-1/2" D



EL74

## EL71

- 1 DPDT relay
- 2 external inputs allow sensors (see accessories) to automatically adjust to environmental conditions
- Pecosoft.EL software and CIM1 Adaptor provide convenient remote programming capabilities (see accessories)
- Also available in NEMA 3R non-metallic enclosure for outdoor use
- Title 24 certified
- Unit dimensions are 4-1/4" W x 7-7/8" H x 3" D



EL71